Multi-Deck Screens

For large capacities and precise cleaning operations



BM&M



Maximum Vibration Control

BM&M dynamically balances all screens. This allows you to install the screen virtually anywhere in your plant, resulting in the lowest possible installation costs.



Maximum Productivity

BM&M puts the drive unit in the center of the machine to get the same screening efficiency over the entire screening surface. With no mechanical gearboxes, **BM&M** operates the screens at 300 RPM versus the conventional 150 - 180 RPM screeners. The consistant motion across the screen and the high speed combines to make the screen very efficient. The result is MAXIMUM efficiency & MAXIMUM capacity for your application.

Features

Maximum Recovery of Clean Acceptable


Product

BM&M builds nothing but screens. Our goal is to recover the maximum amount of good product, as well as removing the rejects. We will test your product and give you a written guarantee of performance at no charge.



3 Year Drive Warranty

BM&M's patented eccentric weight drive assembly is lubricated for life, needing no maintenance. Unlike the competition, **BM&M's** unique static shaft design provides torsional stiffness that ensures long trouble-free service and is the basis for our 3 year warranty.




Ball-Decks

All **BM&M** screens are equipped with "Ball-Decks" to assist in keeping the screen clean.

The active motion propels the captive balls to constantly

strike the underside of the fine screens thus dislodging wedged in particles or near-size plugs.

Depending on the application, **BM&M** Screens can be equipped with a variety of mesh or perforated metal screens in many materials. The Ball-Deck can be provided with optional high temperature or oil resistant 1-3/8" diameter balls.



Specifications

Deck Sizes: 56" x 86"

60" x 120"

- Number of Decks available 1 through 3
- Up to 400 sq. ft. per deck
- Pre-screen and Distribution Box
- Ball-Deck cleaning synthetic balls/hardwood frames
- Enclosed construction
- Quick Change screen access hinged doors at both ends
- Replaceable pans
- 300 RPM standard operating speed at a 11/4" diameter stroke
- Motor 1800 RPM
- Adjustable stroke counter weight assembly c/w maintenance free bearing
- · Construction welded mild steel, fully stress-relieved
- Hollow structural steel support stand
- Custom Discharge Chutes designed for your application


Fully Enclosed Construction


Ensures dust-free installation for a cleaner operating environment and minimum housekeeping.

Options

- Standard and High Capacity Constructions
- Oil Resistant cleaning balls
- Dust Aspiration Ports
- High Temp Construction (180 250 °F)
- · Hanger remote lubrication
- Drive Bearing temperature element

Multi-Deck Screens





Parallel Flow Screens

100	3322P11	3333P11	5011P11	5022P11	5033P11	3322P22	3333P22	5011P22	5022P22	5033P22	5044P11
W	88"	88"	92"	92"	92"	88"	88"	92"	92"	92"	92"
L	120"	123"	151"	154"	157"	125"	128"	157"	162".	165"	170"
Н	96"	108"	86"	98"	110"	102",	121"	93"	112"	130"	141"

High capacity screeners for grains, oil seeds, sawdust, and large capacity bulk powders come in multiple-sizes, with 2,4,6,8, or 12 screens. Up to 600 sq.ft. of screen available!

***BM&M** is a corporation committed to developing a world wide reputation for the design and manufacturing of industry-leading high speed flat rotary screens."





BM&M SCREENING SOLUTIONS

Contact us at:

9377 - 193rd Street, Surrey, BC, Canada V4N 4E7

Toll Free: (800) 663-0323 Phone: (604) 888-8400 Fax: (604) 888-8404

e-mail: sales@bmandm.com Internet: www.bmandm.com

A BM&M Multi-Deck Screen is . . .

- Simple to install
- Simple to operate
- Simple to maintain